



# Light Emitting Diode Lamp



## Specification For Approval

Customer : Apex

Description : LED Lamp

Part Number : B3b-143

Date : 2007. 07. 13

**Approved By:**


--

**Prepared By:**

Checked	QC	Designed	Sales

Date: 2007/7/13

### ★ Package Dimensions



**NOTE:**

- 1.All dimensions are in millimeter.
- 2.Lead spacing is measured where the lead emerge from the package.

### ★ Selection Guide

Part NO.	Chip		Lens Color	Viewing Angle $2\theta$ 1/2(deg)
	Material	Emitted Color		
B3b-143	GaP	Green	Green diffused	40

### Part No:B3b-143

### ★Absolute Maximum Ratings (Ta=25°C)


Parameter	Symbol	MAX. Rating	Unit
Power Dissipation	Pd	80	mW
Continuous Forward Current	IF	30	mA
Pak forward current (10 μs Pulse)	IFM	100	mA
Reverse Voltage	VR	5.0	V
Operating Temperature	Topr	-40~+85	°C
Storage Temperature	Tstg	-40~+85	°C
Lead Soldering Temperature (1.6mm From Case Bottom 260°C For 5 SEC)			

### ★Electric-Optical Characteristics

Parameter	Symbol	Test Condition	MIN	TYP	MAX	Unit
Forward Voltage	VF	IF=20mA		2.1	2.6	V
Reverse Voltage	VR	IR=10uA	5			V
Luminous Intensity	IV	IF=20mA	15	25		mcd
Peak Emission Wavelength	λ P	IF=20mA		565		nm
Spectrum Width Of Half Value	Δ λ	IF=20mA		30		nm

### ★Characteritics Diagrams

Green(GaP)





# Light Emitting Diode Lamp



**Part No:B3b-143**

## ★ Reliability Test

Date: 2007/7/13

No	Item	Test Condition	Test Hours/Cycles	Samples Tested	Acc./Rej
1	Room Temperature DC Oper-ating Life	Ta=25°C, I <sub>F</sub> =20mA	1000 Hrs	76	0/1
2	Thermal Shock	-10°C (5min)→ (10sec)→+100°C (5min)	100 Cycles	76	0/1
3	Temperature Cycle	-40°C (30min) →(5min)→+85 °C (30min)	100 Cycles	76	0/1
4	High Temp./ High Humi. Test	85°C/85%RH	1000 Hrs	76	0/1
5	High Temperature Storage	Ta=100°C	1000 Hrs	76	0/1
6	Low Temperature Storage	Ta= - 40°C	1000 Hrs	76	0/1
7	Soldering Heat	260°C±5°C	5 Seconds	76	0/1