



### DIMENSIONS (mm)

### LAND PATTERNS (mm)

Part No.	A	B	C	D	E	F
JPRD 0402	4.7 ± 0.3	4.7 ± 0.3	2.0 Max.	1.90	1.50	5.30

### SERIES LIST

No.	Part No.	L (μH)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRD 0402-1R0M -	1.0	100	0.045	1.72
2	JPRD 0402-2R2M -	2.2	100	0.075	1.32
3	JPRD 0402-2R7M -	2.7	100	0.105	1.28
4	JPRD 0402-3R3M -	3.3	100	0.110	1.04
5	JPRD 0402-3R9M -	3.9	100	0.155	0.88
6	JPRD 0402-4R7M -	4.7	100	0.162	0.84
7	JPRD 0402-5R6M -	5.6	100	0.170	0.80
8	JPRD 0402-6R8M -	6.8	100	0.200	0.76
9	JPRD 0402-8R2M -	8.2	100	0.245	0.68
10	JPRD 0402-100M -	10	100	0.200	0.61
12	JPRD 0402-120M -	12	100	0.210	0.56
13	JPRD 0402-150M -	15	100	0.240	0.50
14	JPRD 0402-180M -	18	100	0.338	0.48
15	JPRD 0402-220M -	22	100	0.397	0.41
16	JPRD 0402-270M -	27	100	0.441	0.35
17	JPRD 0402-330M -	33	100	0.694	0.32
18	JPRD 0402-390M -	39	100	0.709	0.30

Tolerance : M = ± 20% , M tolerance is standard.

: Revision of specification

### PACKAGE

Type	JPRD 0402
Q'TY/Reel	2,000