



## DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRD 0403	4.7 ± 0.3	4.7 ± 0.3	3.0 Max.	1.90	1.50	5.30

## SERIES LIST

No.	Part No.	L (μH)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRD 0403-1R2M -	1.2	100	0.0236	2.56
2	JPRD 0403-1R8M -	1.8	100	0.0275	2.20
3	JPRD 0403-2R2M -	2.2	100	0.0313	2.04
4	JPRD 0403-2R7M -	2.7	100	0.0433	1.60
5	JPRD 0403-3R3M -	3.3	100	0.0492	1.57
6	JPRD 0403-3R9M -	3.9	100	0.0648	1.44
7	JPRD 0403-4R7M -	4.7	100	0.0720	1.32
8	JPRD 0403-5R6M -	5.6	100	0.1009	1.17
9	JPRD 0403-6R8M -	6.8	100	0.1089	1.12
10	JPRD 0403-8R2M -	8.2	100	0.1175	1.04
12	JPRD 0403-100M -	10	100	0.1283	1.00
13	JPRD 0403-120M -	12	100	0.1316	0.84
14	JPRD 0403-150M -	15	100	0.1490	0.76
15	JPRD 0403-180M -	18	100	0.1660	0.72
16	JPRD 0403-220M -	22	100	0.2350	0.70
17	JPRD 0403-270M -	27	100	0.2610	0.58
18	JPRD 0403-330M -	33	100	0.3780	0.56
19	JPRD 0403-390M -	39	100	0.3837	0.50
20	JPRD 0403-470M -	47	100	0.5870	0.48
21	JPRD 0403-560M -	56	100	0.6245	0.41
22	JPRD 0403-680M -	68	100	0.6990	0.35
23	JPRD 0403-820M -	82	100	0.9148	0.32
24	JPRD 0403-101M -	100	100	1.0200	0.29
25	JPRD 0403-121M -	120	100	1.2700	0.27
26	JPRD 0403-151M -	150	100	1.3500	0.24
27	JPRD 0403-181M -	180	100	1.5400	0.22

Tolerance : M = ± 20% , M tolerance is standard.

: Revision of specification

## PACKAGE

Type	JPRD 0403
Q'TY/Reel	2,000

