



## DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 0703	7.3 ± 0.2	7.3 ± 0.2	3.2 ± 0.2	1.50	4.80	2.20

## SERIES LIST

No.	Part No.	L (μH)	Test Frequency (KHz)	RDC Max. ( )	IDC Max. (A)
1	JPRH 0703-100M -	10	1	0.072	1.68
2	JPRH 0703-120M -	12	1	0.098	1.52
3	JPRH 0703-150M -	15	1	0.130	1.33
4	JPRH 0703-180M -	18	1	0.140	1.20
5	JPRH 0703-220M -	22	1	0.190	1.07
6	JPRH 0703-270M -	27	1	0.210	0.96
7	JPRH 0703-330M -	33	1	0.240	0.91
8	JPRH 0703-390M -	39	1	0.320	0.77
9	JPRH 0703-470M -	47	1	0.360	0.76
10	JPRH 0703-560M -	56	1	0.470	0.68
11	JPRH 0703-680M -	68	1	0.520	0.61
12	JPRH 0703-820M -	82	1	0.690	0.57
13	JPRH 0703-101M -	100	1	0.790	0.50
14	JPRH 0703-121M -	120	1	0.890	0.49
15	JPRH 0703-151M -	150	1	1.270	0.43
16	JPRH 0703-181M -	180	1	1.450	0.39
17	JPRH 0703-221M -	220	1	1.650	0.35
18	JPRH 0703-271M -	270	1	2.310	0.32
19	JPRH 0703-331M -	330	1	2.620	0.28
20	JPRH 0703-391M -	390	1	2.940	0.26
21	JPRH 0703-471M -	470	1	4.180	0.24
22	JPRH 0703-561M -	560	1	4.670	0.22
23	JPRH 0703-681M -	680	1	5.730	0.19
24	JPRH 0703-821M -	820	1	6.540	0.18
25	JPRH 0703-102M -	1000	1	9.440	0.16

Tolerance : M ± 20% , M tolerance is standard.

: Revision of specification

## PACKAGE

Type	JPRH 0703
Q'TY/Reel	1,000