


ME 010-500 Open ends header



Pitch: 5.00mm(0.197inch)





SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 300V	AC 400V
負載電流	Rated Current	Bemessungsstrom	16A	16A
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
焊針	Solder Pin	Lötstift	□1.0mm, Brass, Tin plated	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
PCB板孔徑	PCB Hole Diameter	Lochdurchmesser	φ1.5mm	
UL File No.	E167040			

TABLE

Item No.	A(mm)	A(inch)
ME010-50002	10.0	0.394
ME010-50003	15.0	0.591
ME010-50004	20.0	0.787
ME010-50005	25.0	0.984
ME010-50006	30.0	1.181
ME010-50007	35.0	1.378
ME010-50008	40.0	1.575
ME010-50009	45.0	1.772
ME010-50010	50.0	1.969
ME010-50011	55.0	2.165
ME010-50012	60.0	2.362
ME010-50013	65.0	2.559
ME010-50014	70.0	2.756
ME010-50015	75.0	2.953
ME010-50016	80.0	3.150
ME010-50017	85.0	3.346
ME010-50018	90.0	3.543
ME010-50019	95.0	3.740
ME010-50020	100.0	3.937
ME010-50021	105.0	4.134
ME010-50022	110.0	4.331
ME010-50023	115.0	4.528
ME010-50024	120.0	4.724



PCB Layout

